



# BC201607-ATC4

## SMD Type Blue Emitter

### Features

- Top view 2016 package
- Viewing Angle =  $\pm 60^\circ$
- Compatible with infrared and vapor phase reflow solder process
- High reliability
- Ultra bright Blue
- RoHS compliance



### Applications

- Optical indicator.
- Switch and Symbol Display.

### Description

The BC201607-ATC4 InGaN Blue LED housed in a miniature SMD package. The device has a dominant wavelength of 470 nm LED.


### Package Outline



Anode

Cathode

### Schematic





# BC201607-ATC4

## SMD Type Blue Emitter

### Absolute Maximum Rating at 25°C

Symbol	Parameters	Ratings	Units	Notes
I <sub>F</sub>	Continuous Forward Current	30	mA	
I <sub>FP</sub>	Peak Forward Current	100	mA	1
V <sub>R</sub>	Reverse Voltage	5	V	
T <sub>opr</sub>	Operating Temperature	-40 ~ +85	°C	
T <sub>stg</sub>	Storage Temperature	-40 ~ +100	°C	
T <sub>sol</sub>	Soldering Temperature	260	°C	2
P <sub>D</sub>	Power Dissipation at(or below) 25°C Free Air Temperature	110	mW	

### Electro-Optical Characteristics *TA = 25°C (unless otherwise specified)*

#### Optical Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
I <sub>v</sub>	Luminous Intensity	I <sub>F</sub> =20mA	225	-	450	mcd	3
λ <sub>d</sub>	Dominant Wavelength	I <sub>F</sub> =20mA	460	-	475	nm	4
θ <sub>1/2</sub>	Angle of Half Intensity	I <sub>F</sub> =20mA	-	±60	-	deg	

#### Electrical Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V <sub>F</sub>	Forward Voltage	I <sub>F</sub> =20mA	2.7	-	3.5	V	5
I <sub>R</sub>	Reverse Current	V <sub>R</sub> =5V	-	-	10	μA	

#### Notes:

1. Tolerance of Luminous Intensity ±10%.
2. Tolerance of Dominant Wavelength: ±1nm.
3. Bin Range of Luminous Intensity

Bin Code	Min	Max	Unit	Condition
S2	225	285	mcd	I <sub>F</sub> =20mA
T1	285	360		
T2	360	450		



## BC201607-ATC4

### SMD Type Blue Emitter

---

#### 4. Bin Range of Dominant Wavelength

Bin Code	Min	Max	Unit	Condition
A5	460	465	nm	$I_F=20\text{mA}$
A6	465	470		
A7	470	475		

#### 5. Bin Range of Forward Voltage

Bin Code	Min	Max	Unit	Condition
V9	2.7	2.9	V	$I_F=20\text{mA}$
V10	2.9	3.1		
V11	3.1	3.3		
V12	3.3	3.5		

Tolerance of Forward Voltage:  $\pm 0.1\text{V}$ .



## Typical Characteristic Curves




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5





Figure 6



## Typical Characteristic Curves






# BC201607-ATC4


## SMD Type Blue Emitter

### Package Dimension *All dimensions are in mm, unless otherwise stated*



Note: Tolerance unless mentioned is  $\pm 0.1$ mm

### Recommended Soldering Mask *All dimensions are in mm, unless otherwise stated*



Note: Tolerance unless mentioned is  $\pm 0.1$ mm

### Ordering Information

Part Number	Description	Quantity
BC201607-ATC4	Tape & Reel	4000 pcs




# BC201607-ATC4

## SMD Type Blue Emitter


### Reel Dimension

All dimensions are in mm, unless otherwise stated



### Tape Dimension

All dimensions are in mm, unless otherwise stated



Note: Tolerance unless mentioned is  $\pm 0.1\text{mm}$



## BC201607-ATC4

### SMD Type Blue Emitter

#### Label Form Specification

The label form is a rectangular template for product labeling. It features the CT Micro International Corporation logo at the top left. The text 'MSL-X' and 'MADE IN CHINA' is at the top right. The form contains several fields for product identification: CPN (Customer Part Number), Part no (CTM Production Number), Serial no (Production Number), Lot no (Lot number), Qty (Packing Quantity), Date Code (Manufacture Date), IV (Bin Code of Luminous Intensity), WD (Bin Code of Dominant Wavelength), and VF (Bin Code of Forward Voltage). Each field is followed by a series of vertical bars representing a barcode. A QR code is located in the center-right area. At the bottom right, there are RoHS and Pb-free compliance logos.

CT Micro  
International Corporation

MSL-X  
MADE IN CHINA

CPN: XXXXXXXXXXXXXXXXX  
|||||

Part no: XXXXXXXXXXXXXXXX  
|||||

Serial no: XXXXXXXXX  
|||||

Lot no: XXXXXXXXX  
|||||

Qty: XXXXXX Date Code: YWWJ  
|||||

IV: XX WD:XX VF:XX  
|||||

QR Code

RoHS Pb-free

CPN : Customer Part Number  
Part no: CTM Production Number  
Serial no: Production Number  
Lot no: Lot number  
Q'ty: Packing Quantity  
Date Code: Manufacture Date  
IV : Bin Code of Luminous Intensity  
WD : Bin Code of Dominant Wavelength  
VF : Bin Code of Forward Voltage  
MADE IN CHINA: Production Place

#### Storage Condition


1. Do not open moisture proof bag before the products are ready to use.
2. The moisture barrier bag should be stored at 30°C and 90%R.H. max. before opening.  
Shelf life of non-opened bag is 12 months after the bag sealing date.
3. After opening the moisture barrier bag floor life is 168h at 30°C/60%RH. max. Unused LEDs should be resealed into moisture barrier bag. (Refer to J-STD-020 Standard)
4. If the moisture absorbent material has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the J-STD-033 Standard conditions.





## BC201607-ATC4 SMD Type Blue Emitter

### Reflow Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (Tsmin)	150°C
Temperature Max. (Tsmax)	200°C
Time (ts) from (Tsmin to Tsmax)	60-120 seconds
Ramp-up Rate (tL to tP)	3°C/second max.
Liquidous Temperature (TL)	217°C
Time (tL) Maintained Above (TL)	60 – 150 seconds
Peak Body Package Temperature	260°C +0°C / -5°C
Time (tP) within 5°C of 260°C	30 seconds
Ramp-down Rate (TP to TL)	6°C/second max
Time 25°C to Peak Temperature	8 minutes max.

### DISCLAIMER



## BC201607-ATC4

### SMD Type Blue Emitter

---

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

---

CT MICRO ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICRO INTERNATIONAL CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*