



Reflection Type Photo-Interrupter

Features

- Optimal sensing distance : 3mm
- High reliability
- High sensitivity
- Fast response time
- Reflective with Phototransistor output
- Spectral range of sensitivity: 700-1100nm
- RoHS compliance



Description

The PIR4030S-D3 is a reflection type photo-interrupter which consist of an infrared emitting diode and an NPN silicon photo-transistor. The device has a long focal distance for this family of devices and has a SMD package, suitable for reflow soldering.


Applications

- Infrared sensor
- Printers
- Switch scanner

Package Outline



Schematic





Reflection Type Photo-Interrupter

Absolute Maximum Rating at 25°C

Symbol	Parameters	Ratings	Units	Notes
T _{opr}	Operating Temperature	-40 ~ +85	°C	
T _{stg}	Storage Temperature	-40 ~ +100	°C	
T _{sol}	Soldering Temperature	260	°C	1
Emitter				
I _F	Continuous Forward Current	50	mA	
V _R	Reverse Voltage	6	V	
P _D	Power Dissipation at(or below) 25°C Free Air Temperature	75	mW	
Detector				
P _C	Collector Power Dissipation	75	mW	
I _C	Collector Current	20	mA	
B _V CEO	Collector-Emitter Voltage	35	V	
B _V ECO	Emitter-Collector Voltage	6	V	

Electro-Optical Characteristics TA = 25°C (unless otherwise specified)

Emitter Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V _F	Forward Voltage	I _F =4mA	1.00	1.15	1.40	V	
		I _F =50mA	1.10	1.30	1.60		
I _R	Reverse Current	V _R =5V	-	-	10	μA	
λ _p	Peak Wavelength	I _F =4mA	-	940	-	nm	

Detector Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
B _V CEO	Collector-Emitter Breakdown	I _C =100μA	35	-	-	V	
B _V ECO	Emitter-Collector Breakdown	I _E =100μA	6	-	-	V	
I _{CEO}	Dark Current	V _{CE} =20V	-	-	100	nA	
I _{CEOD}	Operating Dark Current	V _{CE} =2V, I _F =4mA	-	-	500	nA	
λ _p	Peak Sensitivity	V _{CE} =2V	700	900	1100	nm	



Electro-Optical Characteristics $T_A = 25^\circ\text{C}$ (unless otherwise specified)


Transfer Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
I_C	Collect Current	$V_{CE}=2V$, $I_F=4mA$ $D=4mm$	60	280	500	μA	2
t_r	Rise Time	$V_{CE}=2V$, $I_C=0.1mA$ $R_L=1K\Omega$	-	30	-	μs	3
t_f	Fall Time		-	40	-		
t_{on}	Turn on Delay Time		-	32	-		
t_{off}	Turn off Delay Time		-	42	-		


Notes:

1 : Soldering time ≤ 5 seconds.

2 : Test condition :









3 : Test circuit:











Typical Characteristic Curves






Typical Characteristic Curves






Package Dimension *All dimensions are in mm, unless otherwise stated.*







Recommended Soldering Footprint *All dimensions are in mm, unless otherwise stated*





Label Form Specification

	MADE IN CHINA
Part no.: XXXXXXXXX 	Bin Code: X
Serial no.: XX000XX 	
Lot no.: XXXXXXXXX 	
Q'ty: XXXX pcs 	
Date Code: 20XXXXX 	
	  

Part no: CTM Production Number

Serial no: Production Number

Lot no: Lot number

Q'ty: Packing Quantity

Date Code: Manufacture Date

Bin Code: Ic Ranks

MADE IN CHINA: Production Place

Storage Condition


1. Do not open moisture proof bag before the products are ready to use.
2. The moisture barrier bag should be stored at 40°C and 90%R.H. max. before opening.
Shelf life of non-opened bag is 12 months after the bag sealing date.
3. After opening the moisture barrier bag floor life is 72h at 30°C/60%RH. max. Unused LEDs should be resealed into moisture barrier bag. (Refer to J-STD-020 Standard)
4. If the moisture absorbent material has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the J-STD-033 Standard conditions.



Reflection Type Photo-Interrupter

Ordering Information


Reel Dimension *All dimensions are in mm, unless otherwise stated*





Reflection Type Photo-Interrupter

Reflow Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (T _{smin})	150°C
Temperature Max. (T _{smax})	200°C
Time (t _s) from (T _{smin} to T _{smax})	60-120 seconds
Ramp-up Rate (t _L to t _P)	3°C/second max.
Liquidous Temperature (T _L)	217°C
Time (t _L) Maintained Above (T _L)	60 – 150 seconds
Peak Body Package Temperature	260°C +0°C / -5°C
Time (t _P) within 5°C of 260°C	30 seconds
Ramp-down Rate (T _P to T _L)	6°C/second max
Time 25°C to Peak Temperature	8 minutes max.



Reflection Type Photo-Interrupter

DISCLAIMER

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

CT MICRO ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICRO INTERNATIONAL CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*